

Automate And Secure Your Entrance In Style



LOWER MAINTENANCE

BlueSpeed V2 motor uses lowest possible rotation speed (RPM) that reduces mechanical wear and effectively eliminates any maintenance servicing on the motor.



2 TIMES SAFER

DDS (Dual Detection Safety) uses dual sensor to auto reverse the arm if blocked by obstacle. This is a important double safety feature to prevent further damage in the event when arm hit car or pedestrian.



205

MINIMUM DOWNTIME

DSP (Dual Spring Pull) and quick access to local spare parts, rest assured the barrier gate will be up and running most of the time.



ENHANCED FUNCTIONALITY

Built-in DC 12V 5A power supply for LED arm and traffic detector. Recommended LED arm for enhanced visibility.



Better protection for your car

Arm will swing out when hit directly by vehicle from the front.

Foam lining installed underneath our arm is specially designed with the right density to absorb bigger impact force to avoid dent when arm accidentally hit your car.







Work harder and longer for you

Compared to other types of motor, BlueSpeed AC motor is simpler, more affordable and stronger to easily lift up the arm even with additional signage. It does not use any carbon brush and therefore is maintenance free. It is designed with efficient air cooling system to support higher traffic flow at your building.






More convenient

Telescopic capability shorten the arm length to eliminate the need of big truck to transport arm to site. Less hassle for you when ordering replacement arm.

During power failure, MAG manual release clutch design make it more convenient for you to unlocked and manually open or close arm without removing whole top cover.

Manual release



ACCESSORIES

ORDERING INFO



License plate recognition camera



Xclone long range reader



Xclone 12V power supply



Mid range reader



EWI loop detector



Push button



Foam lining



Signboard Traffic light

TRAFFIC DETECTOR

Open / close Max arm length & Arm swing out Model speed type BG652 1.8 sec 4m straight Yes BG657 4.5m straight 3 sec Yes BG658 6 sec 6m straight No BG652 90 1.8 sec 4m folding No BG657_90 4m folding No 3 sec BG657 180 3.5m folding No 3 sec BG658_FE 6 sec 4.5m fence No

Left side	BG652-L, BG657-L, BG658-L, BG652-L90, BG657-L90, BG657-L180, BG658-LFE
Right side	BG652-R, BG657-R, BG658-R, BG652-R90, BG657-R90, BG657-R180, BG658-RFE

Certified by:





BRD03 DualRay and LED Display

FASTER INSTALLATION

No road cutting for loop coil. Can be easily mounted outside on barrier gate housing in less than 30 minutes. This help you save more money in installation labour cost



Able to detect any obstacle including people to effectively auto reverse barrier arm earlier "before" hitting anyone.

Authorised Dealer:

Copyright © 2024 Magnet Security & Automation Sdn Bhd All rights reserved.

All specification, drawing and product info are subject to change without prior notice.







